

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 February 2005 (10.02.2005)


PCT

(10) International Publication Number  
WO 2005/011966 A1

- (51) International Patent Classification<sup>7</sup>: B29D 11/00, (74) Agent: FITZPATRICKS; 1 Blythwood Square, Glasgow G2 4AD (GB).  
B65B 5/04
- (21) International Application Number: PCT/GB2004/003211
- (22) International Filing Date: 23 July 2004 (23.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0317301.0 24 July 2003 (24.07.2003) GB  
60/525,184 28 November 2003 (28.11.2003) US
- (71) Applicant (for all designated States except US): PROVIS LIMITED [GB/GB]; 5 Livingstone Boulevard, Hamilton Industrial Technology Park, Blantyre G72 0BP (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HAMILTON, Ronald, Shade [GB/GB]; Provis Limited, 5 Livingstone Boulevard, Hamilton International Technology Park, Blantyre G72 0BP (GB). McFARLANE, Stephen, Donald [GB/GB]; Provis Limited, 5 Livingstone Boulevard, Hamilton International Technology Park, Blantyre G72 0BP (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: METHODS AND APPARATUS FOR USE IN CONTACT LENS MANUFACTURE AND PACKAGING



(57) Abstract: An un-hydrated contact lens (110) is removed from a concave mould piece (115) while holding the mould lens-uppermost, by applying a downward force to a flange portion of the mould, applying an upward force (F) to the convex backside of the mould piece. The resulting deformation breaks adhesion between the lens and the concave optical surface of the mould piece, while the lens is captured and removed by a lifting probe (130, 134). Many lenses are processed in parallel. The dry, un-hydrated contact lenses (110) are deposited by the probe (130, 134) into respective packaging blister cavities (145). Each cavity is pre-dosed with a spot of fluid (150). The contact of fluid between lens and receptacle captures the lens consistently in the base of the receptacle, neutralising the disruptive effects of electrostatic charges in particular. With the dry lens (110) in the packaging cavity (145) a finishing head is used comprising adjacent inlet and outlet nozzles (230, 240) for hydrating the lens, for flushing away contaminated hydrating fluid (220), prior to dosing the cavity with packaging fluid (260).

WO 2005/011966 A1